

BAULMANN

New Products 2022/2023

www.baulmann.com 5055/5053





34.162.03-121

Surface:	Brass dull 03	pendant luminaire brass dull
Lamp socket:	for 1 x E27 / 230 V	1 x E27
Voltage:	230 V	shade: made of natural-grey SAND
Protection class:	I	diameter ca. 230 mm, height ca. 240 mm
Safety norm:	CE	



34.177.69

Surface:	Black 69	pendant luminaire black
Lamp socket:	for 1 x E14 / 230 V	1 x E14
Voltage:	230 V	glass opal white, Ø ca. 150 mm
Protection class:	I	
Safety norm:	CE	



64.128.54

Surface:	Dark bronzed 54	wall luminaire dark bronzed
Lamp socket:	for 1 x GU10 / 230 V	1 x GU10 LED
Voltage:	230 V	with adjustable joint
Protection class:	I	reflector: diameter overall ca. 60 mm,
Safety norm:	CE	length ca. 110 mm, incl. Louver grid



83.204.55

Surface:	White 55	ceiling luminaire white
Lamp socket:	for 1 x GU10 / 230 V	1 x GU10 LED
Voltage:	230 V	suspension ca. 150 mm
Protection class:	I	with adjustable joint
Safety norm:	CE	reflector: diameter overall ca. 60 mm, length ca. 110 mm, incl. Louver grid



83.205.69

Surface:	Black 69	ceiling luminaire black
Lamp socket:	for 1 x GU10 / 230 V	1 x GU10 LED
Voltage:	230 V	suspension ca. 300 mm
Protection class:	I	with adjustable joint
Safety norm:	CE	reflector: diameter overall ca. 60 mm, length ca. 110 mm, incl. Louver grid



64.255.57

Surface:	Black-gold 57	wall luminaire black/gold
Lamp socket:	for 1 x GU10 / 230 V	1 x GU10
Voltage:	230 V	reflector inside gold matt painted,
Protection class:	I	Ø ca. 95/70 mm, with adjustable joint
Safety norm:	CE	Ø wall box ca. 90 mm



64.256.54-902

Surface:	Dark bronzed 54	wall luminaire dark bronzed
Glass:	opal-white glass sphere, glossy	2 x G9
Voltage:	230 V	opal-white glass sphere glossy
Protection class:	I	Ø ca. 95 mm
Safety norm:	CE	



64.256.69-903

Surface:	Black 69	wall luminaire black
Glass:	clear glass sphere, rippled	2 x G9
Lamp socket:	for 2 x G9 / 230 V	clear glass sphere, rippled
Voltage:	230 V	Ø ca. 95 mm
Protection class:	I	
Safety norm:	CE	



Picture similar

64.480.03

Surface:	Brass dull 03	LED reading light brass dull
Lamp socket:	1 x LED integrated / 230 V / 1 W	round LED-head, incl. 1 w LED warm white
Length:	140 mm	LED driver included
Width:	50 mm	wall box black, dim. ca. 140 x 50 mm
Switch:	with integrated on/off switch	with integrated on/off-switch
Wattage:	1 W	
Voltage:	230 V	
Protection class:	III	
Safety norm:	CE	



Picture similar

64.480.54

Surface:	Dark bronzed 54	LED reading light dark bronzed
Lamp socket:	1 x LED integrated / 230 V / 1 W	round LED-head, incl. 1 w LED warm white
Length:	150 mm	LED driver included
Width:	40 mm	dimensions wall box ca. 140 x 50 mm
Switch:	with integrated on/off switch	with integrated on/off-switch
Wattage:	1 W	
Voltage:	230 V	
Protection class:	III	
Safety norm:	CE	



64.511.69

Surface:	Black 69	LED reading light black
Lamp socket:	2 x LED integrated / 230 V / 3 W	cylindric bar, length ca. 250 mm,
Wattage:	3 W	with acrylic glass cylinder
Dimming:	not dimmable	with adjustable joint
Voltage:	230 V	incl. 2 x LED 350 mA / ca. 3 w, 3.000 K
Protection class:	III	LED driver (added as loose part)
Safety norm:	CE	fixation from the front with two screws



64.512.69

Surface:	Black 69	LED reading light black
Lamp socket:	2 x LED integrated / 230 V / 3 W	cylindric bar, length ca. 250 mm,
Wattage:	3 W	with acrylic glass cylinder
Dimming:	not dimmable	with adjustable joint
Voltage:	230 V	incl. 2 x LED ca. 3 watt 3.000 K
Protection class:	III	LED driver included
Safety norm:	CE	diameter wall box ca. 90 mm



64.513.69

Surface:	Black 69	wall luminaire black
Lamp socket:	2 x LED integrated / 230 V / 8 W	incl. 2 x 4 watt LED warm white
Width:	45 mm	LED driver included
Height:	220 mm	
Outreach:	65 mm	
Wattage:	8 W	
Voltage:	230 V	
Protection class:	I	
Safety norm:	CE	



65.114.06

Surface:	light bronzed 06	Wandleuchte Hell brüniert
Lamp socket:	1 x LED integrated / 230 V / 6 W	incl. LED 12 V / ca. 6 watt warm white
Length:	600 mm	LED driver included
Width:	65 mm	length/width/extension ca. 600/65/98 mm
Outreach:	98 mm	protection rating IP 44
Wattage:	6 W	
Dimming:	not dimmable	
Voltage:	230 V	
Protection class:	I	
Safety norm:	CE	



65.115.54

Surface:	Dark bronzed 54	wall luminaire dark bronzed
Lamp socket:	1 x LED integrated / 230 V / 9 W	incl. LED 12 V / ca. 9 watt warm white
Length:	900 mm	LED driver included
Width:	65 mm	length/width/extension ca. 900/65/98 mm
Outreach:	98 mm	protection rating IP 44
Wattage:	9 W	
Dimming:	not dimmable	
Voltage:	230 V	
Protection class:	I	
Safety norm:	CE	



84.152.69

Surface:	Black 69	recessed luminaire black, adjustable
Lamp socket:	1 x LED integrated / 230 mA / 6 W	incl. 6 watt LED warm white
Diameter:	90 mm	plus LED driver (accessories)
Switch:	with rocker switch	outside diameter ca. 90 mm
Wattage:	6 W	cut-out ca. 75 mm
Voltage:	230 mA	min. height inside ceiling ca. 100 mm
Protection class:	III	
Safety norm:	CE	



88.206.01

Surface:	Brass polished 01	recessed downlight polished brass
Lamp socket:	1 x LED integrated / 1 W	incl. 1W LED warm white
Diameter:	35 mm	plus LED driver (accessories)
Wattage:	1 W	diameter ca. 35/30 mm
Protection class:	III	recessing height ca. 35 mm
Safety norm:	CE	



88.207.14

Surface:	Chrome 14	recessed downlight chrome
Lamp socket:	1 x LED integrated / 1 W	incl. 1W LED warm white
Diameter:	35 mm	plus LED driver (accessories)
Wattage:	1 W	diameter ca. 35/30 mm
Protection class:	III	min. height inside ceiling ca. 26 mm
Safety norm:	CE	height ca. 10 mm